

QUARTZ SINK SUGGESTED MAINTENANCE

GENERAL CARE

Wash your sink using warm water, a non-abrasive liquid cleaner or detergent and a soft cloth or non-abrasive woven nylon pad. Your sink may be cleaned as often as it is used.

HEAVY STAINS

Most stains incurred during normal use can be washed away with water and a mild cleaner such as Comet, BON AMI, Bar Keepers Friend, Soft Scrub and a green Scotch Brite pad.

Some stains may require a diluted solution of bleach. Do not leave concentrated bleach soaking in your sink as it could cause discoloration.

To prevent staining and discoloration, always rinse your sink after use with clean warm water.

FOR YOUR DARK QUARTZ SINK WITH WHITE STAINS

Degreasing The first step is degreasing of the sink. Please use for this purpose a soft, dampened cloth, a sponge or, in case for example of dried stains a nailbrush and some liquid washing up detergent. Move in circular motions with a little pressure over the sink's surface. Rinse the sink with tap water. If necessary, please repeat this step.

Descaling The second step is descaling of the sink. Please use a common descaler and be sure, that no formic acid is contained. Then use the descaler according to the manufacturer's instructions. Rinse well with tap water, if necessary repeat this step.

Metal Abrasion Metal abrasion from your pans, your cool pot or other cookware may occur. You can easily remove this by using a magic sponge (dirt eraser) which is very gentle to the sink's surface. Damp the magic sponge with pure water and treat the metal abrasions with little pressure until there are no more residues.

Intense Clean The third step is the intense cleaning of the sink, if necessary. Therefore please spill hot water a thumb thick high in the sink and dilute a portion of common dishwasher detergent. Let this rest for approx. 1 hour or overnight, then rinse well.

Sealing The fourth step is the sealing of the cleaned sink. Therefore the sink needs to be absolutely clean and dry. Please apply a stone sealer for closed surfaces even and thin over the sink's surface by using a chamois or a micro fibre cloth. (Please also follow the included instructions).

Ready The freshly treated sink should be allowed to rest for min. 6 hours so that the sealing can react with the sink's surface. Now your sink again repels all the stains and dirt that may affect it. Just use a sponge or cloth and some soapy water to remove any residues.

****Please do not use any strong abrasives cleaning creams or powders, concentrated caustic soda, formic acid or anything highly corrosive. Do not use wire wool or steel soap pads as steel particles can become embedded in your sink and rust.***

****Please always be careful while using household cleaning agents and acids! Always follow the instructions of use of the manufacturer! Sensitive persons should wear gloves while using detergent!***

REMOVING OF STUBBORN LIMESTONE DEPOSITS FROM THE SINK

For removing stubborn limestone deposits use a mixture of citrix acis and vinegar.

Preparing of the Mixture Take four table-spoons of Citric and solve this in 0.2 litre of hot water. Then add the same amount of white vinegar and give the misture a little stir.

Application Close the drain of the sink and pour this mixture into the boowl and add hot water until the bow's surface is covered with liquid. Let this work for min 1 hour. After this drain off the liquid and rinse well with cold water, give the surface a little brush with a washing-up brush.

Now your sink is free of any Limestone Deposit.

For additional information please contact us. Phone: (678) 445-4638.